

As standard included

<input type="checkbox"/>	BV410T-GS02-QM-S	18221168979	203 dpi model
<input type="checkbox"/>	BV410T-TS02-QM-S	18221168980	300 dpi model

<input type="checkbox"/>	BV420T-GS02-QM-S	18221168981	203 dpi model
<input type="checkbox"/>	BV420T-TS02-QM-S	18221168982	300 dpi model



BV410T

- Thermal transfer 4" desktop printer
- Graphic display
- User interface with 2x LED and 3x key
- USB and LAN interfaces
- Dimensions & weight: 200 x 267 x 198.3 mm, 2.9 kg



BV420T

- Thermal transfer 4" desktop printer
- User interface with 3x LED and 2x key
- USB and LAN interfaces
- Dimensions & weight: 200 x 267 x 198.3 mm, 2.9 kg

Model Specific Options

BV410T (white case)

<input type="checkbox"/>	BV214-F-QM-S	18221165454	Full cutter
<input type="checkbox"/>	BV214-P-QM-S	18221165455	Partial cutter
<input type="checkbox"/>	BV914T-H-QM-S	18221165465	Peel-off module
<input type="checkbox"/>	BV914T-AC-QM-S	18221165467	AC adapter cover
<input type="checkbox"/>	BV704T-RFID-U4-EU-S	18221165471	UHF band RFID R/W kit

BV420T (black case)

<input type="checkbox"/>	BV224-F-QM-S	18221165434	Full cutter
<input type="checkbox"/>	BV224-P-QM-S	18221165435	Partial cutter
<input type="checkbox"/>	BV924T-H-QM-S	18221165466	Peel-off module
<input type="checkbox"/>	BV924T-AC-QM-S	18221165468	AC adapter cover

Common Options

Connectivity and media stand

<input type="checkbox"/>	BV700-WLAN-QM-S	18221165439	Wi-Fi interface (802.11 a/b/g/n)
<input type="checkbox"/>	BV700T-BLTH-QM-S	18221165469	Bluetooth interface (V5.2 + BR/EDR)
<input type="checkbox"/>	BV700-RS-QM-S	18221165441	RS-232C interface
<input type="checkbox"/>	BV904-PH-QM-S	18221165438	External 8" media stand (black only)